



Wyndmaster 300-2

Automatic Take-up System



FEATURES

- Non-stop production capabilities
- Dual strip
- Eight Reel Capacity
- Dancer loop and tension control
- Part / Length counter with operator alert system
- Programmable operator interface with diagnostics
- 800 IPM feed rate
- Quick release reel flanges
- Casters and floor brakes
- Quick and simple product changeover
- Unattended automatic strip transfer

OPTIONS

- Single spindle paper interleaf
- Dual spindle paper interleaf with auto splice
- Sonic non-contact loop control
- Part count non-contact loop control
- Wrapped accumulator
- Non-contact accumulator
- High speed / high torque motors
- Part strip locator
- Collapsible mandrel
- In-feed puller with encoder
- Tail retention gripper
- Over center locking latch fingers
- Material component selection for corrosive environments



Customized Products
For Any Applications!

jcrautomation.com

JCR Automation
1426 Ryan Rd
New Haven, IN 46774
Phone: 260-493-6606





Wyndmaster 300-2

Specifications

POWER REQUIREMENTS

110 VAC, single phase, 10A

AIR SUPPLY

80 PSI @ 5 SCFM

MATERIAL WIDTH (MAX)

3 Inches.

REEL DIAMETER (MAX)

24 Inches

FEED RATE

800 1 PM with out accumulator

PAINT COLOR

Vista Green (or Per Customer Requirements)

PRODUCT FEED

Left to right or right to left (must be speci ed).

SPINDLE CONFIGURATION

Tooled To Customers Reel

SPINDLE MOTOR

1/8 HP, 28:1 ratio, 76 RPM, DC



Customized Products
For Any Applications!

jcrautomation.com

JCR Automation
1426 Ryan Rd
New Haven, IN 46774
Phone: 260-493-6606

