

## Wyndmaster 324P

## Four Spindle Automatic Take-up System



#### **FEATURES**

- Automatic Cut and Transfer
- **Overwind Operation**
- Non-Contact Loop Control
- Single Strip Operation
- Four Reel Capacity
- Programmable Paper Tension
- Four Spindle Operator Start Paper Interleaf
- **Tangential Product Feeder**
- Part Counter with Operator Alert System
- Programmable Operator Interface with Diagnostics
- Quick Release Reel Flanges
- Sample Strip with Programmable Cut Location

#### **OPTIONS**

- **Dancer Loop Control**
- High Speed / High Torque Motors
- Material Component Selection for Corrosive Environment









# **Wyndmaster 324P**

### **Specifications**

#### **POWER REQUIREMENTS**

120 VAC, single phase, 15A

#### **AIR SUPPLY**

80 PSI

#### **MATERIAL WIDTH (MAX)**

3 Inches (others available on request)

#### **REEL DIAMETER (MAX)**

36 Inches (others available on request)

#### **FEED RATE CAPABILITY**

800 IPM Without Accumulator

#### **REEL CENTER CORE**

5.0 inches (others available upon request)

#### **FEED DIRECTION**

Left to right or right to left (Per Customer Requirements)

#### **SPINDLE MOTORS**

76 RPM, 1/8 HP, DC

#### **SPINDLE DIAMETER**

0.75 Inches (Standard, others available on request)









