

Wyndmaster 400

Automatic Take-up/ Traverse & Pancake



FEATURES

- Non-stop production capabilities
- Unattended automatic strip transfer
- Three reel capacity
- Dancer loop and tension control
- Part /Length counter with operator alert system
- Programmable operator interface with diagnostics
- 800 IPM feed rate
- Quick release reel flanges
- · Casters and floor brakes
- · Quick and simple product changeover

OPTIONS

- Single spindle paper interleaf
- Dual spindle paper interleaf with auto splice
- Sonic non-contact loop control
- Part count non-contact loop control
- In-feed puller with encoder
- Tail retention gripper
- · Over center locking latch fingers

Optional paper interleafing and paper layering systems are available for product separation. A dual spindle continuous feed pancake paper interleafing system includes an auto splice feature for uninterrupted paper coil transfers. The sheet feeder measures, cuts, and feeds individual sheets between each layer on the traverse reels.









Wyndmaster 400

Specifications

POWER REQUIREMENTS

120 VAC, single phase, 25 A

AIR SUPPLY

80 PSI @ < 5SCPM

PRODUCT WIDTH (MAX)

3 Inches

SPINDLE DIAMETER

(Per Customers request)

FEED RATE

800 IPM 600 IPM w / Paper Layering 300 PPM w / 30' Product Accumulator

REEL CAPABILITIES

Pancake - 32" Diameter, 3" Wide Traverse - 24" Diameter, 11" Wide

FEED DIRECTION

Left to right or right to left (Per Customer Requirements)

SPINDLE MOTORS

1/8 HP, 1750 RPM, DC

DRIVE PIN

(Per Customers request)

CORE DIAMETER

(Per Customers request)

PAINT COLOR

(Per Customers request)

PANCAKE PAPER OPTION

25" Diameter, 3" Wide

TRAVERSE PAPER LAYERING OPTION

16" Diameter, 5 -10" Wide

icrautomation.com







