



# Coilmaster 9000

## Model 9000 Stock Take-Up



### FEATURES

- 9000 pound weight capacity
- 65" coil diameter capacity
- 16" material width
- Edge control system
- Programmable stock tension constant or variable
- 12" diameter by 16" wide expanding mandrel
- Urethane coated infeed guide roller
- Microprocessor controlled with operator interface

### OPTIONS

- Back flange (aluminum or steel)
- Paper payout spindle
- 16" diameter expanding mandrel
- Second roller for S-wrap infeed
- Tail clamp
- Custom mandrels and flange arrangements also available



Customized Products  
For Any Applications!

[jcrautomation.com](http://jcrautomation.com)

JCR Automation  
1426 Ryan Rd  
New Haven, IN 46774  
Phone: 260-493-6606



# Coilmaster 9000

## Specifications

### POWER REQUIREMENTS

240 VAC, three phase, 20A

### AIR SUPPLY

Required with tail clamp only (80PSI Minimal CFM)

### STOCK SIZE

1 to 16 width.

### COIL SIZE

12 Standard ID, 16 Optional ID, 65 Maximum OD,  
16 Wide, 9000 pound weight capacity

### FEED RATE

90 FPM with 12 mandrel standard Other feed rate  
available at customer request.

### MANDREL

Standard 12 expandable 11 1/2 to 12 1/2  
Optional 16 expandable 15 1/2 to 16 1/2

### PRODUCT FEED

Left to right or right to left (must be specified).

### EDGE CONTROL SYSTEM

Analog optical edge sensor (manually set by the operator) with programmable offset, ball screw actuator driven by a 1/2 HP DC motor and controller, and linear slides.

Automatically adjusts mandrel position to provide near perfect coil geometry.

### SPINDLE MOTOR

Programmable torque/tension, 5HP brushless DC drive 0 to 9,500 in.-lb. torque at the spindle. Optional 5HP brushless DC drive 0 to 15,000 in.-lb. torque at the spindle. Programmable tension set point at minimum and maximum coil diameter.



Customized Products  
For Any Applications!

[jcrautomation.com](http://jcrautomation.com)

JCR Automation  
1426 Ryan Rd  
New Haven, IN 46774  
Phone: 260-493-6606

